



Weiler Labeling Systems

Customer listening... Customized thinking



The WLS **TLP** top leaflet placer affixes leaflets accurately and efficiently to the top of containers at speeds up to 450ppm. It is available either as an integrated or stand-alone unit.

The heart of the system is a servomotor-driven star wheel which positively extracts leaflets from an accumulation magazine. The **TLP** design eliminates the need for adjustable stop pins and the problems associated with vacuum extraction. Hot melt glue is automatically applied to each container prior to leaflet application. The **TLP** is electronically driven and encoded to the parent machine allowing it to accurately place leaflets at varying line speeds.

The **TLP** can be configured with a variety of options such as a larger "Rack" feeder which stores up to forty-five minutes of leaflets before operator reloading is required while allowing for replenishment while the unit is running, as well as various verification sensors.

Backed by WLS' reputation of quality, impeccable service and customer care, and industry leading extended warranty coverage, the **TLP** is built to meet the most challenging leaflet application demands.

1256 North Church Street
Moorestown, NJ 08057 USA
+1 856 273 3377
+1 856 231 9883 fax
sales@weilerls.com
www.weilerls.com

TLP
Top Leaflet Placer
High-speed, Precise Leaflet Application



TLP
**Top Leaflet
Placer**

SALES AND SERVICE

WLS Sales and Service assures responsive and comprehensive technical assistance in solving your labeling application problems, servicing your WLS equipment, and providing a full line of compatible systems supplies.

SPECIFICATIONS

- Leaflet Size:
 - Width - 1/2" to 2" (13mm to 51mm)
 - Height - 1" to 2" (25.4mm to 51mm)
- Standard Rack Feeder:
 - 12-pockets
- Application Speed:
 - Up to 450ppm
- Surface Speed:
 - 0-2500 in/min (0 to 63.5 m/min)

FEATURES

- Retrofit able onto most labeling systems, or supplied as a stand-alone system
- Power vertical and ratchet horizontal adjustments
- 12-pocket rack feeder
- Nordson "ProBlue" hot melt applicator
- Tool-less quick change leaflet star wheel
- Servomotor-driven
- Accurate placement at varying line speeds
- Low leaflet sensor
- No proprietary electronics

OPTIONS

- Adjustable leaflet star wheel
- Leaflet inspection
- Verification of code on the leaflet adhesive side
- Missing leaflet-on-product sensor
- Product counter
- Leaflet counter
- FAT/DDS/IQOQ documentation
- UL, seismic and CE certification